

BALUSTRADE

INSTALLATION GUIDE

Balustrade must comply with Standard AS/NZ1170.1:2002 Please check with your local Council regarding specific requirements.


Tools Required: Pencil, String-line, Tape Measure, Spirit Level, Drill, Spanners, Tek Gun/Drill, Angle Grinder/Hacksaw

GETTING STARTED

Calculate the number of panels and posts required.

Mark the position of each flanged post.


Panels fixed to a wall will need a Top Rail Panel Bracket.



ADJUST TO FIT

- Mark any special lengths including 50mm space for the sleeve and panel bracket. Cut the rails to the required length
- 2. When fitting a corner post it may be necessary to cut the fixed post off the next panel.

















HOW TO INSTALL YOUR BALUSTRADE


- Starting at one end, install the first panel. Fix securely to a wall (A), or fit an End Post (B) if required.
- 2. Fit the next panel by inserting the sleeve into the Top Capping (B). Fit the Panel Bracket to the bottom capping before fixing in place. (C). Fix in place using 8.8 x 20mm tek screws or 4.8 x 9.6mm large flange aluminium rivets. Use a minimum of 3 fixings per rail. Repeat with other panels, ensuring panels are straight, level and fitted together correctly.
- 3. Secure all posts to floor.
 For concrete, secure with
 M10 x 100mm stainless steel
 dyna-bolts or chem-set studs (Pic D).
 For timber secure with M10 x 100mm
 coach screws into joists
 or M10 x 100mm bolts and nuts
 if securing from underneath.
 Fit chocks under the deck and use
 large flat washers between nuts and
 timber (Pic E). Securely tighten and
 check for rigidity.
- 4. Fix corner and end posts as required.











BALUSTRADE SPECIFICATIONS

Standard Panels – 2000mm wide (including fixed post) x 1010mm high Corner Posts – 50x50x1010mm flanged bottom – sleeved top (90°)

End Posts – 50x50x1010mm flanged bottom – sleeved top (1-way)

Top Rail Panel Bracket 50x25 single lug (2-hole



Bottom Rail Panel Bracket 38x25 single lug (2-hole)





